


BVM6610P



High Quality and Reliable Modules Due to Thorough Design and Stringent Quality Control


- Withstand up to 5400 Pa snow load and 2400 Pa wind load
- 1000V DC
- Three times of EL inspection on every cell and module for defect free
- Type 1 fire-rating per UL 1703 edition 3
- High salt and ammonia resistance certified by TUV Rheinland
- 0~+5 W guaranteed positive tolerance on nameplate power output

Warranty

- 12- year product warranty
- 25-year linear power output warranty

Comprehensive Certificates for Products and Management

- UL 1703, IEC 61215, IEC 61730, CEC listed, MCS and CE
- ISO 9001 for Quality Management Systems
- ISO 14001 for Environmental Management Systems



Electrical Characteristics STC

	BVM6610P-250	BVM6610P-255	BVM6610P-260	BVM6610P-265	BVM6610P-270
Maximum Power(Pmax)	250W	255W	260W	265W	270W
Maximum Power Current(Imp)	8.31A	8.39A	8.47A	8.52A	8.57A
Maximum Power Voltage(Vmp)	30.1V	30.5V	30.7V	31.2V	31.6V
Short Circuit Current (Isc)	8.85A	8.95A	9.01A	9.20A	9.31A
Open Circuit Voltage (Voc)	37.5V	37.8V	38.0V	38.3V	38.5V
Module Efficiency	15.4%	15.7%	16.0%	16.19%	16.49%
Power Tolerance	0~+5W	0~+5W	0~+5W	0~+5W	0~+5W

STC: AM1.5, Irradiance 1000W/m², 25 °C

Electrical Characteristics NOCT

	BVM6610P-250	BVM6610P-255	BVM6610P-260	BVM6610P-265	BVM6610P-270
Maximum Power(Pmax)	187W	189W	194W	197W	201W
Maximum Power Current (Imp)	6.63A	6.65A	6.76A	6.78A	6.85A
Maximum Power Voltage (Vmp)	28.2V	28.4V	28.6V	29.0V	29.3V
Short Circuit Current (Isc)	7.04A	7.15A	7.22A	7.36A	7.45A
Open Circuit Voltage (Voc)	34.5V	34.8V	35.0V	35.3V	35.6V

NOCT: AM1.5, Irradiance 800W/m², 20 °C, Wind speed 1m/s)


Packing Information

Pieces per pallet	26
Pallets per container(40HQ)	28
Pieces per container(40HQ)	728
Pallets weight/size	1177.3lb/66.93*44.49*45.28 inch



Maximum Ratings

Operating Temperature	-40 °F~185 °F
Maximum Series Fuse Rating	15A
Maximum System Voltage	1000V DC

I-V Curves at Different Irradiances(260W)
Test temperature:25°C




Irradiance:AM1.5,1000W/m²(260W)



Mechanical Characteristics

Solar Cell	Polycrystalline 6.14x6.14inch,60(6x10) pcs in series
Glass	High transparency, low iron, tempered glass 3.2mm(0.13inch)
Frame	Anodized aluminum alloy
Junction Box	IP65/IP67 rated, with 3 bypass diode
Output cable	4 mm ² (EU)/12 AWG(US), 35.43inch long
Connector	MC4 compatible
Dimension	64.57x39.06x1.57inch
Weight	40.79lb



Thermal Characteristics

Pmax Temperature Coefficient	-0.43%/K
Voc Temperature Coefficient	-0.33%/K
Isc Temperature Coefficient	+0.05%/K
NOCT	113±3.6 F